

RX21-25SFD 25 1/2" Deep, 21RU Mobile Equipment Rack includes: Casters, Side Handles, and solid doors.

The RX21-25SFD mobile cabinet is ruggedly constructed of 16-ga. CRS and include heavy-duty casters. Equipped with a front pair of 11-gauge CRS adjustable mounting rails tapped 10-32 on standard E.I.A. 5/8"- 5/8"-1/2" spacing.

Optional RR21 rear mounting rails are available for additional support. Front-to-rear mounting rail supports have slotted cutouts to easily adjust rail depth and to provide open raceways for containing vertically run wire and cable.

The RX21 features the additional benefit of having the supports positioned 19" apart to accept standard panel width accessories mounted in vertical orientation.

Cabinet is 25 1/2" deep and has a vertical panel space height of 36 7/8"

It features one pair of recessed, hinged, and rubber-padded steel grips on each side (four total) for transport convenience.

Easy wiring access is provided through three wire isolation holes (two, 1 1/2" dia., and one oblong 1-1/2" x 3") in the rear base flange.

The units'

four, oversized, heavy-duty casters, two of which are locking, ensure smooth mobility, and have a load capacity of 175 lb. each – 700 lb. total weight capacity.

Also include vented and removable locking doors, as well as vented top-front and top-rear flanges. Surface mounting front door is 1" deep to provide clearance for equipment knobs and handles which protrude up to 1 1/2" from the front of the rail.

Cabinet is finished in #962 black epoxy. Tech Data Specifications

16-ga. CRS Frame Manufactured to E.I.A. Standards

Four, 4" Heavy-Duty Casters (175 lb. cap./ea.)

Includes 1 Pair Adjustable, 11-ga., Front-to-Rear Mounting Rails

Mounting Rail Supports with Slotted Cut-Outs for Vertical Wire Management

Perforated Front and Rear Top Flanges, Sides and Rear Door Provide Ventilation and Dissipation of Equipment-Generated Heat

Removable Front and Rear Doors (Right or Left-Hand Hinging) are Identically Keyed for Security and Convenience

RR21 optional rear mounting rails available

Rubber-Padded Steel Grip "Road Handles" (2 Per Side)

Standard Rack Includes Base, Top Panel, Side Panels, Casters, Front and Rear Doors
Three Wire Isolation Holes Located on Bottom of Rear Panel for External Wire Access
Welded Frame for Long-Lasting Durability

Height 45 3/4" (116.205 cm)
Width 22 5/16" (56.67502 cm)
Depth 25 1/2" (64.77 cm)
Rack Spaces 21
Usable Depth 24" (60.96 cm)

CAD Drawing

©2010 Atlas Sound LP. All Rights Reserved • Products